

An Intelligent Deep Learning Framework for Crop Disease Prediction Using Convolutional Neural Networks

Pradeep Kandu, Nitinmaan, Vivek Kumar, Hitesh Singh

Noida Institute of Engineering and Technology, Greater Noida, Uttar Pradesh, India

B.Tech (CSE-R): Pradeep Kandu, Nitinmaan

Email:
pradeepkandu9794@gmail.com
nitinmaan843@gmail.com
vivek.bansal1977@gmail.com
hitesh.singh.85@gmail.com

Received: 17.04.2026

Revised: 22.05.2026

Accepted: 30.05.2026

Doi: 10.68419/cb/v1i2/4-10

Early and precise identification of crop diseases plays a pivotal role in maintaining agricultural productivity, food security and sustainable agricultural systems. Conventional approaches to crop disease diagnosis involve visual inspection, which can be slow, labor-intensive, and prone to human error, particularly in fluctuating environmental conditions. This article introduces a smart deep learning model for automatic detection of crop diseases with Convolutional Neural Networks (CNNs). Our approach takes advantage of the superior image recognition and feature extraction abilities of CNN models to predict the presence of disease and health in plants based on leaf images. A comprehensive dataset of crop leaf images is used, including various disease and healthy classes. Leaf images are preprocessed and augmented to improve model generalization and resilience to lighting, pose and background clutter. The CNN model is trained with fine-tuned hyperparameters and performance is assessed using metrics like accuracy, precision, recall and F1-score. The experimental findings show that the proposed model produces high classification accuracy and is capable of detecting complex disease patterns, even in the early disease stage. The proposed system offers a scalable, affordable, and non-invasive method for monitoring diseases in the field. Moreover, it can be incorporated with mobile or IoT systems to facilitate precision farming and help farmers make informed decisions for disease control. This research is a step towards the creation of autonomous agricultural systems and the use of deep learning for improving crop health assessment and productivity.

Keywords: *Crop Disease Detection, Deep Learning, CNN, Image Classification, Smart Agriculture, Precision Farming*

1. Introduction

Agriculture is a critical sector for global food security, economic growth and sustainable development, as it supports a significant portion of the world's population. But crop productivity is increasingly threatened by climate change, pests and, more importantly, plant diseases. Plant diseases not only impair the quality and quantity of crop yield, but also cause economic losses and food supply chain interruptions. Timely and precise diagnosis of these diseases is crucial to limit losses and enable effective containment strategies. Conventional disease detection approaches, involving manual identification by farmers or agronomists, are time-consuming, labour-intensive, prone to subjectivity, and require expertise, making them less suitable for large-scale and real-time applications [11], [18].

Over the past decade, the field of Artificial Intelligence (AI) and Deep Learning has transformed agriculture through the development of automated and smart disease detection. In particular, Convolutional Neural Networks (CNNs) have proved to be effective in image classification tasks as they can learn hierarchical features from the image data. Rather than traditional machine learning techniques that rely on pre-engineered features, CNNs learn intricate features such as color changes, texture abnormalities and lesion patterns from plant leaf images. This has led to the development of more accurate and robust disease prediction models for diverse

crop species such as wheat, cauliflower, cotton and apple leaves [4], [5], [9].

A number of studies have shown the success of deep learning approaches in crop disease identification. Intelligent systems like DeepCrop and DCrop have demonstrated the integration of deep learning models with web applications for disease diagnosis, which can be easily used by farmers [1], [2]. Likewise, adapted deep learning models have shown good performance in disease classification and early detection for particular crops such as cotton [3]. Improved CNN models and hybrid models, such as CNNs combined with Conditional Random Fields (CRFs) and Vision Transformers, have also improved disease detection accuracy by taking into account spatial and contextual features [13], [16]. Additionally, real-time systems for disease identification using enhanced CNN models have been proposed for crops like corn and grape, showcasing the potential for implementing these models in real-world agricultural settings [12], [14].

Recent research has also focused on novel methods, including thermal images, Internet of Things (IoT) integration, and multispectral data, for enhancing disease detection accuracy. For instance, CNN models using thermal images have been able to detect diseases that are not apparent in conventional RGB images [6], and IoT-based systems have provided real-time monitoring and predictive capabilities in smart agriculture [19], [20]. Furthermore, deep

learning models have been integrated with crop monitoring platforms to predict yield and determine plant health, showcasing their potential use in precision farming [8], [10]. However, there is still a need to enhance model performance under different environmental conditions, including variations in lighting, background, and image resolution, which impact the model's generalization capabilities.

To address these issues, this study aims to develop an intelligent crop disease prediction system that employs Convolutional Neural Networks (CNNs) to predict the disease from plant leaf images. The main goal is to build an efficient and accurate model for early detection of disease, facilitating timely action and thus preventing crop losses. The system harnesses deep learning's ability to automatically extract discriminative features from images, removing the need for human intervention and enhancing scalability. Additionally, the aim is to make the system scalable for deployment in real-time through mobile or web apps to be used by farmers and other stakeholders in the agricultural sector.

The data set in this study consists of annotated images of healthy and diseased plant leaves, covering a range of diseases such as bacterial, fungal, viral and leaf spots. Preprocessing methods, including resizing, normalization and augmentation, are also employed to improve model accuracy. This allows the model to accommodate changes in leaf orientation, background, and lighting conditions. The CNN model is trained and validated using common metrics for model performance and it exhibits good prediction accuracy and classification performance.

The importance of this work is that it may help promote sustainable farming practices through an automated, accurate, and scalable disease-detection system. Early detection helps farmers take proactive measures, curbing the overuse of pesticides and protecting the environment. Additionally, the application of deep learning in agriculture is in line with the concept of smart farming, which leverages data and technology to improve efficiency and productivity.

The rest of the paper is structured as follows: Section 2 gives the background and related work on deep learning for crop disease detection. The data and preprocessing used in the study are explained in Section 3. Section 4 outlines the CNN-based approach, model architecture and training process. Section 5 presents the experimental results and evaluation. Lastly, Section 6 concludes this paper and suggests future work, which includes incorporating transfer learning and real-time systems.

2. State of the Art

Recent years have seen rapid improvements in using deep learning for predicting crop diseases, motivated by a growing demand for efficient, accurate and scalable farming solutions. Convolutional Neural Networks (CNNs) have emerged as a preferred model because of their capacity to learn features from leaf images. Pioneering systems like DCrop introduced deep learning architectures for disease

prediction, showing better prediction accuracy than conventional machine learning approaches and showing the potential of using AI in smart agriculture systems [2]. Refining this further, later systems such as DeepCrop introduced web platforms to support real-time disease prediction, enhancing farmer engagement [1].

In recent years, attention has shifted towards improving model performance and transferability using fine-tuning and hybrid models. For example, fine-tuned CNN models for cotton disease detection have improved their accuracy using transfer learning, allowing faster training with comparable accuracy [3]. Likewise, research on cauliflower and wheat crops have adopted deep CNN models to accurately detect early diseases, highlighting the need for early detection to prevent widespread crop losses [4], [5]. These examples highlight the use of deep learning models for detecting disease patterns such as texture changes, colour changes and lesion patterns.

Beyond traditional RGB images, other data sources have been used to enhance detection accuracy. The use of thermal images and improved CNN models has allowed non-visible disease symptoms to be detected, offering a new data source [6]. Similarly, hyperspectral and multispectral systems, while heavy on computational loads, have been found to improve detection accuracy through the analysis of biochemical changes in plant tissues. Real-time applications for disease detection systems, using modified CNN architectures, have also been developed for apple, corn and grape, showcasing their potential to be used in the field [9], [12], [14].

Hybrid and other advanced deep learning approaches have also improved disease prediction. Hybrid CNN models that combine CRFs have enhanced spatial coherence of the disease prediction, especially in complex backgrounds [16]. Likewise, hybrid models incorporating Vision Transformers (ViT) and CNNs have improved feature extraction by focusing on local and global image features [13]. These developments suggest a trend towards more complex architectures that can overcome issues like intra-class and inter-class variations.

The use of deep learning in conjunction with the Internet of Things (IoT) is also a potential avenue. IoT-based systems enable real-time monitoring of crops and prediction of diseases, aiding precision farming [19], [20]. Further, smart systems have been designed for sustainable crop monitoring and prediction of disease, yield and environmental factors [8], [10]. These systems highlight the possibility of using multiple data streams for holistic agriculture analysis.

However, there are still issues with the state-of-the-art. Existing models perform well in controlled environments but are often limited in terms of their generalisation ability in practical scenarios with diverse lighting, occlusions and backgrounds. Moreover, the computational demands of sophisticated models restrict their use on low-power devices, like smartphones and edge devices. Finally, there is a need for integrated systems that combine disease detection with

decision-making systems (e.g., treatment advice, predictive analytics).

In terms of analysis, the literature suggests that there is an evolution from simple CNN models to hybrid and multi-

modal approaches. Nevertheless, there is a need for efficient, light, and fast models that are accurate and can be used in the field. Overcoming these challenges is crucial for the deployment of AI-based disease prediction systems.

Table 1: Comparative Analysis of State-of-the-Art Crop Disease Prediction Methods

Ref.	Methodology	Application Area	Key Contribution	Strengths	Limitations
[1]	Deep CNN + Web App (DeepCrop)	General Crop Diseases	Real-time web-based disease prediction	Accessible, scalable	Depends on internet connectivity
[2]	CNN Framework (DCrop)	Smart Agriculture	Early DL-based disease prediction system	High accuracy vs traditional ML	Limited generalization
[3]	Fine-tuned CNN (Transfer Learning)	Cotton Disease	Improved accuracy with reduced training time	Efficient learning	Crop-specific model
[4]	Advanced Deep CNN	Cauliflower Disease	Early-stage disease detection	High precision	Dataset dependency
[5]	CNN Model	Wheat Disease	Accurate classification of wheat diseases	Robust feature extraction	Limited environmental adaptability
[6]	Thermal Imaging + CNN	Plant Disease Detection	Detects non-visible disease patterns	Multi-modal analysis	Expensive hardware
[7]	Deep CNN	General Crop Diseases	Standard CNN-based classification	Simple implementation	Moderate performance
[8]	ML + Smart Monitoring	Millet Crop	Integrated disease + monitoring system	Sustainable agriculture support	Indirect disease classification focus
[9]	Improved CNN	Apple Leaf Disease	Real-time detection system	Field applicability	Computational cost
[10]	Deep Learning Platform	Yield + Disease Prediction	Integrated prediction system	Multi-functional	Complex system design
[11]	Review Study	Plant Disease Detection	Comprehensive survey of CNN methods	Broad insights	No implementation
[12]	CNN-based System	Corn Disease	Real-time disease detection	Practical deployment	Limited dataset scope
[13]	CNN + Vision Transformer	Seed Disease	Hybrid feature extraction	Improved accuracy	High complexity
[14]	Improved CNN	Grape Disease	Real-time detection	High accuracy	Sensitive to noise
[15]	Deep Encoder Network	Seasonal Crops	Disease classification	Handles seasonal variation	Computationally intensive
[16]	CNN + CRF Hybrid	Plant Disease	Spatial consistency improvement	Better segmentation	Increased complexity
[17]	CNN (Mobile-based)	Field Images	Real-world mobile-based classification	Practical usability	Lower accuracy in wild conditions
[18]	Survey (CNN-based)	Plant Diseases	Overview of DL techniques	Identifies research gaps	No experimental results
[19]	IoT + ML Framework	Pearl Millet	Real-time disease monitoring	Smart farming integration	Infrastructure dependency
[20]	DL + IoT	Plant Disease Prediction	Integrated smart agriculture system	Automation + monitoring	Deployment challenges

4. Proposed Methodology

The Crop Disease Prediction system is a well-organized deep learning framework that employs Convolutional Neural Networks (CNNs) to classify plant leaf diseases. The proposed system combines data preprocessing, feature extraction, model training and evaluation for effective disease prediction. The system uses a dataset of over 6,000 labeled crop leaf images sourced from the PlantVillage dataset, which is classified into five categories: Early Blight, Late Blight, Healthy, Bacterial Spot and Leaf Mold. The images display various visual features such as spots, blemishes, and fungi, which are used to define the classes.

The approach starts with an extensive preprocessing step to normalise and optimise the data. Images are resized to a consistent size of 128×128pixels to fit the CNN model's input dimensions and to speed up processing. Images are also normalized by scaling the pixel values from 0-255 to 0-1, which accelerates convergence of training and stabilizes gradients. The dataset is split into training and validation sets

with an 80:20 ratio using the ImageDataGenerator class, while maintaining a balanced representation of each class of disease. To enhance model performance and prevent overfitting, the training images are augmented by rotating, flipping, and zooming the images. This helps the network learn more invariant features that are less affected by changes in lighting, orientation, and background. To extract features and perform classification, a custom CNN model is designed. It has three consecutive convolutional layers, each with 32, 64 and 128 filters. Each of these is followed by a MaxPooling layer that downsamples the spatial dimensions while preserving the most important features. This permits the extraction of low-level features like edges and gradients and more complex high-level features such as disease-specific textures and patterns. The feature maps are then flattened and fed into a dense (fully connected) layer with a ReLU activation function, allowing the model to learn non-linear features and enhance its classification performance.

To improve the model's resilience and avoid overfitting, a Dropout layer with a rate of 0.3 is added to randomly drop



out 30% of neurons during training. This helps prevent the model from overfitting to certain features and enhances its ability to generalize to new cases. The output layer employs the Softmax activation function to classify the five classes of diseases, returning a probability distribution for each class. The model is compiled with the Adam optimizer, offering adaptive learning rates that enable efficient and stable training, and the categorical cross-entropy loss function, appropriate for multi-class classification tasks. The model is trained for 15 epochs using a batch size of 32, enabling gradual learning and optimization of the model's parameters. Validation accuracy, confusion matrix, and classification report are used to assess the model's performance, offering both numerical and visual representations of its performance.

The experiment is conducted in the Google Colab environment, with GPU acceleration to speed up the training process. Software packages like TensorFlow and Keras are employed for model construction, with NumPy, Matplotlib, Seaborn and Scikit-learn used for data manipulation and visualization. The experimental framework provides replicable and consistent results. The CNN-based approach proposed attains a validation accuracy of 91.87%, showcasing robust classification performance and feature extraction capabilities. The model is chosen as the final model for crop disease prediction based on its accuracy and generalisation capability, presenting a practical and scalable approach for agricultural disease prediction.

5. Results and Discussion

The performance of the developed Convolutional Neural Network (CNN) model for multi-class classification of crop diseases was assessed using the validation dataset. The CNN model reached a validation accuracy of 91.87%, showing a high ability to classify various leaf diseases. The training and validation accuracy curves demonstrate steady progress over the 15 epochs, suggesting stable training and low overfitting. The minimal difference between training and validation accuracy indicates effective generalization. The confusion matrix shows that most of the disease classes were accurately classified with high precision and recall values. But there were some misclassifications between visually similar diseases like Early Blight and Late Blight due to similarities in symptoms. The classification report also supports the balanced performance for all five classes of diseases. In summary, the findings suggest that the CNN model successfully learns significant visual characteristics like changes in leaf colour, lesion shapes and textures. The model's accuracy of 91.87% confirms the effectiveness of deep learning approaches for crop disease classification. The system offers a good platform for real-time disease monitoring in agriculture




Figure 1: Training and Validation Accuracy Analysis of CNN Model

Figure 1 shows the training and validation accuracy curves of the proposed CNN model during 15 epochs, which reflect the learning and generalisation performance. The training accuracy steadily improves from around 59% at the beginning (epoch 0) to nearly 97% by the end of the training process (epoch 15). This gradual increase suggests that the model is successfully capturing hierarchical features in the dataset, from simple features like edges and colour differences, to more complex disease-specific features. The validation accuracy also exhibits a good learning curve, with a steep rise in the early epochs from approximately 76% to over 90%. This initial growth is a result of the model's capacity to apply learned features to new data. Following this, the validation accuracy plateaus between 89% and 91%, with slight variations. This is a good sign, as it indicates that the model has converged at an optimal learning point without compromising its learning performance. Another notable feature of the graph is the close proximity of the training and validation accuracy in the later epochs. This suggests that the model is not overfitting and generalizes well on the validation data. The lack of a significant gap or sudden separation between the curves also suggests that the model is not overfitting to the training data, and the regularization methods, such as the use of dropout and data augmentation, are successful. The peak validation accuracy is around 91%, which is very close to the overall test accuracy of 91.87%. The close agreement between validation and test results further demonstrates the model's stability and generalization performance. Moreover, the stability and consistency of the curves suggest that the optimization of the model is well-balanced and that the hyperparameters (such as learning rate, batch size, optimizer, etc.) are well selected for the task.




Figure 2: Training and Validation Loss Analysis of CNN Model

In Figure 2, the changes in training and validation loss over 15 epochs are depicted, giving insight into the ability of the proposed CNN model to reduce the prediction error during the learning phase. The training loss exhibits a steady and gradual decrease from an initially high value to a much lower value in the last epochs. This consistent decrease suggests that the model is effectively adjusting its weights and learning to extract relevant features from the crop leaf images. The validation loss also exhibits a similar pattern, with a steep decline in the early epochs, indicating a quick improvement in the model's ability to learn and generalize from the training data. Over time, the validation loss becomes more stable, suggesting that the model is reaching a close-to-optimal solution. While there are slight fluctuations after around the 10th epoch, these are minor and not a sign of instability. Crucially, there is no abrupt rise in the validation loss, which indicates that the model is not overfitting. It's also worth noting that the training and validation loss curves are very similar during the training phase. This indicates that the model is able to learn and generalize well, extracting useful disease features without overfitting to the training data. The smoothness of the two curves also indicates the efficacy of the preprocessing and regularization methods (data augmentation and dropout). The convergence stability, error reduction and generalization ability of the proposed CNN model are evident in Figure 2. The smooth and steady curve of both loss functions verifies the convergence of model training and its suitability for crop disease classification in practical applications.




Figure 3: Confusion Matrix Analysis of CNN-Based Crop Disease Classification

The confusion matrix, shown in Figure 3, offers an insight into the performance of the proposed CNN model in classifying various crop disease classes. This matrix shows the number of true positive samples on the diagonal, and false positives on the off-diagonal. High values along the diagonal lines indicates that the model has high precision and is able to accurately classify most of the disease classes. In particular, the model performs exceptionally well in classifying Tomato_Bacterial_spot and Tomato_Late_blight with a greater number of instances being correctly predicted. This suggests that these disease categories are visually more distinguishable, enabling the model to learn discriminative features (such as disease patterns, color, texture) more readily. These findings demonstrate the ability of the CNN model to learn disease-specific features from leaf images. But the confusion matrix also indicates some challenges. There are significant misclassifications between similar-looking diseases, particularly Early blight and Late blight for both tomato and potato. These can have similar visual symptoms including spots and blotches, which can be challenging even for humans to distinguish. Moreover, a few healthy leaves are misclassified as diseased, which may be due to data noise, lighting conditions, or minor leaf damage that is often mistaken for early signs of disease.

These few errors notwithstanding, the prediction distribution suggests the model keeps a high degree of accuracy, with low error rates. The confusion matrix offers insights to improve the model further, such as by including a wider range of healthy and diseased samples in the training set, using more sophisticated feature extraction methods, or assigning weights to different classes to improve discrimination between visually similar diseases. Overall, Figure 3 demonstrates that the proposed CNN successfully classifies multiple classes, and that the majority of mistakes occur when the classes are visually similar. This confirms the model's overall performance and suggests potential improvements for future research.




Figure 6: Class Distribution Analysis of Crop Disease Dataset

Figure 6 is a bar plot that shows the number of samples in each crop disease category in the dataset, offering insights into the dataset's balance and how it affects model performance. The histogram demonstrates that the dataset is fairly balanced, with similar numbers of samples in each class. This balance ensures that the model encounters a reasonable number of samples from all crop disease categories during the training process, enabling learning of distinct features for each category. The balance in the dataset is important to avoid bias in the model towards a specific category. Training models on imbalanced datasets may result in biases towards categories with more samples, and may not perform well on underrepresented classes. But in this scenario, the pseudo-balanced representation across classes promotes equitable learning and encourages balanced classification performance across all classes, as shown in the confusion matrix and accuracy scores.

Moreover, the equal proportion of each category in the dataset improves the model's ability to generalize, allowing it to make accurate predictions on unseen samples. This can be seen from the consistent validation accuracy and loss curves in the previous figures. The adequate representation within classes also enhances the statistical significance of the data and mitigates overfitting.

5. Discussion

The experimental outcomes show the CNN-based system for crop disease prediction achieved high accuracy, as well as strong generalization and robustness. The predicted accuracy of 91.87% for the validation set demonstrates good generalization for multiple types of diseases. This performance is a result of the CNN's ability to capture hierarchical features of the crop leaf images, such as changes in colour, lesion shapes and textures. The training and validation accuracy curves show a consistent learning curve. As the training accuracy steadily rises and the validation accuracy quickly approaches and settles at 90-91%, we can see the model effectively learns significant features without overfitting. The small difference between training and validation accuracy indicates that the model is effectively generalising. This is corroborated by the loss curves, which show that both training and validation loss consistently

declines and approaches a stable level, exhibiting smooth optimization and convergence of model parameters. The confusion matrix offers more insights on class-level performance. The model performs well for visually distinct disease classes like Tomato_Bacterial_spot and Tomato_Late_blight, which can be easily identified visually. But there is some level of confusion between visually similar diseases, such as Early blight and Late blight across crops. These misclassifications reflect a challenge in image-based diagnosis, where disease symptoms like spots and yellowing can be similar. Moreover, a few healthy images are misclassified as diseased, which indicates that the model is sensitive to subtle visual differences or noise. The class distribution plot shows that the dataset is well-balanced, which is essential for ensuring equitable model performance across different classes. This balance helps ensure the model has sufficient training examples for each class, which helps avoid biased predictions. This is reflected in the consistent validation accuracy and balanced classification performance among classes. Data augmentation also plays a crucial role in improving the model's generalisation ability by introducing realistic variability, such as rotation, illumination changes, and scaling. This enhances the model's adaptability to various environmental factors, making it more practical for real-world applications. In addition, the normalization and fixed dimensions of the input lead to quicker training times. While the results are encouraging, there are some limitations. Similar visual patterns among different disease classes can impact the model performance, resulting in misclassification. Further, lighting, background variations and image quality affect the accuracy of the model. The issues encountered indicate that while the model performs well under controlled settings, it needs to be improved for use in the complex and variable real-world scenarios. Potential improvements could include the use of transfer learning with pre-trained models to enhance feature learning and prediction performance. The addition of attention mechanisms may enable the model to focus on particular areas of images to predict the presence or absence of a disease, thereby avoiding confusion between similar classes. Also, integrating image data with other information like environmental variables (temperature, humidity) or multispectral data may enhance the prediction accuracy. In summary, the result discussion confirms that the proposed CNN model is an effective and efficient solution for crop disease prediction. The model exhibits good accuracy, generalizability, and potential for real-world applications. At the same time, the study also shows the limitations of the proposed system and the need for future research to further improve the accuracy, reliability and adaptability to practical deployment.

6. Conclusion

In this study, we presented an efficient and smart Convolutional Neural Network (CNN) model for automatic prediction of crop diseases from leaf images. The system was trained on a dataset containing more than 6,000 images of various crops affected by multiple diseases and was thoroughly tested using accuracy, loss, confusion matrix, and

other classification evaluation metrics including precision, recall, and F1-score. These findings indicate that the model has learnt to recognise complex visual features such as textural differences, lesion shapes and colours of various crop diseases. The CNN model reached a validation accuracy of roughly 91.87%, showcasing its excellent classification performance and potential for use in practical agricultural settings. The training and validation curves showed smooth convergence and the small differences between them confirmed the model's generalization ability and slight overfitting. The loss curves also confirmed effective optimization, with steady reduction in loss and balanced learning. Furthermore, the confusion matrix showed that the model achieved good classification for most classes, with limited errors observed between visually similar diseases, like early and late blight. The equal representation of classes in the dataset and the use of data augmentation techniques played a crucial role in improving the model's accuracy. This allowed the system to be resilient to slight changes in image orientation, lighting and background, often encountered in field conditions. In conclusion, the proposed system offers an affordable, scalable and non-destructive method for early detection of crop diseases, enabling early intervention and better management practices. While the results are encouraging, there are still some limitations, including the ability to differentiate diseases that have similar visual symptoms and adapt to diverse environmental conditions. Future research will aim to improve the model's accuracy by using transfer learning models (such as ResNet or EfficientNet), adding real-field data to the dataset, and incorporating attention mechanisms to better localise features. Additionally, the model can be integrated into a mobile or edge computing platform to provide real-time crop disease monitoring, enhancing its usability for farmers. In summary, this research highlights the great potential of deep learning in revolutionising conventional farming systems into smart agricultural systems. The CNN model paves the way for the development of more sophisticated crop disease prediction systems, which can be used to promote sustainable farming, enhance crop yields, and ensure food security.

References

- Islam, M. M., Adil, M. A. A., Talukder, M. A., Ahamed, M. K. U., Uddin, M. A., Hasan, M. K., ... & Debnath, S. K. (2023). DeepCrop: Deep learning-based crop disease prediction with web application. *Journal of Agriculture and Food Research*, 14, 100764.
- Pallagani, V., Khandelwal, V., Chandra, B., Udutalapally, V., Das, D., & Mohanty, S. P. (2019, December). DCrop: A deep-learning based framework for accurate prediction of diseases of crops in smart agriculture. In *2019 IEEE international symposium on smart electronic systems (iSES)(formerly inis)* (pp. 29-33). IEEE.
- Islam, M. M., Talukder, M. A., Sarker, M. R. A., Uddin, M. A., Akhter, A., Sharmin, S., ... & Debnath, S. K. (2023). A deep learning model for cotton disease prediction using fine-tuning with smart web application in agriculture. *Intelligent Systems with Applications*, 20, 200278.
- Kanna, G. P., Kumar, S. J., Kumar, Y., Changela, A., Woźniak, M., Shafi, J., & Ijaz, M. F. (2023). Advanced deep learning techniques for early disease prediction in cauliflower plants. *Scientific Reports*, 13(1), 18475.
- Ashraf, M., Abrar, M., Qadeer, N., Alshdadi, A., Sabbah, T., & Khan, M. (2023). A convolutional neural network model for wheat crop disease prediction. *Computers, Materials, & Continua*, 75(2), 3867.
- Bhakta, I., Phadikar, S., Majumder, K., Mukherjee, H., & Sau, A. (2023). A novel plant disease prediction model based on thermal images using modified deep convolutional neural network. *Precision Agriculture*, 24(1), 23-39.
- Dhanalakshmi, N., Jeyanthi, M., & Prabu, A. V. (2021). Crop disease prediction using deep convolution neural network. *Psychology and Education Journal*, 58(1), 4273-8.
- Mishra, S., Volety, D. R., Bohra, N., Alfarhood, S., & Safran, M. (2023). A smart and sustainable framework for millet crop monitoring equipped with disease detection using enhanced predictive intelligence. *Alexandria Engineering Journal*, 83, 298-306.
- Jiang, P., Chen, Y., Liu, B., He, D., & Liang, C. (2019). Real-time detection of apple leaf diseases using deep learning approach based on improved convolutional neural networks. *Ieee Access*, 7, 59069-59080.
- Lee, S., Jeong, Y., Son, S., & Lee, B. (2019). A self-predictable crop yield platform (SCYP) based on crop diseases using deep learning. *Sustainability*, 11(13), 3637.
- Joseph, D. S., Pawar, P. M., & Pramanik, R. (2023). Intelligent plant disease diagnosis using convolutional neural network: a review. *Multimedia Tools and Applications*, 82(14), 21415-21481.
- Mishra, S., Sachan, R., & Rajpal, D. (2020). Deep convolutional neural network based detection system for real-time corn plant disease recognition. *Procedia Computer Science*, 167, 2003-2010.
- Bhadana, D., & Purandhar, N. (2021). An enhanced deep learning framework integrating Vision Transformers-CNN for accurate seed-borne disease prediction in crops. *International Journal of Business Management and Economic Review*, 4(2), 260.
- Xie, X., Ma, Y., Liu, B., He, J., Li, S., & Wang, H. (2020). A deep-learning-based real-time detector for grape leaf diseases using improved convolutional neural networks. *Frontiers in plant science*, 11, 751.
- Khamparia, A., Saini, G., Gupta, D., Khanna, A., Tiwari, S., & de Albuquerque, V. H. C. (2020). Seasonal crops disease prediction and classification using deep convolutional encoder network. *Circuits, Systems, and Signal Processing*, 39(2), 818-836.
- Rezk, N. G., Attia, A. F., El-Rashidy, M. A., El-Sayed, A., & Hemdan, E. E. D. (2022). An efficient plant disease recognition system using hybrid convolutional neural networks (CNNs) and conditional random fields (CRFs) for smart IoT applications in agriculture. *International Journal of Computational Intelligence Systems*, 15(1), 65.
- Picon, A., Alvarez-Gila, A., Seitz, M., Ortiz-Barredo, A., Echazarra, J., & Johannes, A. (2019). Deep convolutional neural networks for mobile capture device-based crop disease classification in the wild. *Computers and Electronics in Agriculture*, 161, 280-290.
- Dhaka, V. S., Meena, S. V., Rani, G., Sinwar, D., Ijaz, M. F., & Woźniak, M. (2021). A survey of deep convolutional neural networks applied for prediction of plant leaf diseases. *Sensors*, 21(14), 4749.
- Kundu, N., Rani, G., Dhaka, V. S., Gupta, K., Nayak, S. C., Verma, S., ... & Woźniak, M. (2021). IoT and interpretable machine learning based framework for disease prediction in pearl millet. *Sensors*, 21(16), 5386.
- Gupta, A. K., Gupta, K., Jadhav, J., Deolekar, R. V., Nerurkar, A., & Deshpande, S. (2019, March). Plant disease prediction using deep learning and IoT. In *2019 6th International Conference on Computing for Sustainable Global Development (INDIACom)* (pp. 902-907). IEEE.